

1650 Buried Splice Closure

Model 1650 Series



NAME

CNI-BSC 1650-S KIT

CNI-BSC 1650-A KIT

CNI-BSC 1650-A2 KIT

CNI-BSC 1650-A4 KIT

CNI-BSC 1650-B2 KIT

ORDER NUMBER

BSC-1650-S

BSC-1650-A

BSC-1650-A2

BSC-1650-A4

BSC-1650-B2

CNI 1650 Series Buried Splice Closures are designed with a reinforced heat-shrinkable wraparound sleeve coated internally with a hot-melt adhesive that provides a watertight seal to the cable sheath. This Buried Closure restores the integrity of the cable sheath opening in a “non-pressurized” buried cable environment and can accommodate 25-3,600 pair cable splices.



ORDERING INFORMATION

CNI ORDERING NUMBER	CLOSURE SIZE	SPLICE OPENING (INCHES)	MIN. CABLE DIAMETER* (INCHES)	MAX. CABLE DIAMETER* (INCHES)	APPROX. CABLE RANGE (PAIRS)	APPROX. AMT. OF ENCAPSULANT REQUIRED
BSC-1650-S	S	12.0	0.35	1.10	6-25	500 grams
BSC-1650-A	A	12.0	0.48	2.20	25-100	750 grams

BSC-1650-A2	A2	21.0	0.48	2.20	25-200	1,500 grams
BSC-1650-A4	A4	37.0	0.48	2.20	25-400	2,500 grams
BSC-1650-B2	B2	21.0	1.10	3.75	200-400	3,000 grams

*** Cable range and encapsulant required will vary upon cable type, gauge, connector type, and splice configuration**