MAQS G.fast Splitter with Dual Primary Protection Module

Model SA-7012-2001

NAME

ORDER NUMBER

MAQS G.fast Splitter with Dual Primary Protection Module SA-7012-2001



BENEFITS

- G.fast Splitter and Dual Protection in single module
- Superior lightning and surge protection
- Backwards compatible to VDSL2 and ADLS2+



The MAQS Module provides both Line and POTS primary protection and splitter in one module that offer quick and easy configuration changes.

The combination of both GDT and Solid state primary protectors coordinate to offer superior lightning and surge protection.

The Splitter is specifically built for the demanding technology of G.fast by maximizing performance and data rates and is also backward compatible to VDSL2 and ADSL.

The Splitter module fits in any position on the 24-port mounting frame.

SPECIFICATIONS

| DIMENSIONS | 26.5 x 14.4 x 145.2 mm 1.04 x .57 x 5.72" |
|--------------------------|--|
| OPERATING TEMPERATURE | -40 to +65 °C -40 to +149 °F |
| WEIGHT | 42.5g (1.5oz) |
| CAPACITY | 1 Subscriber loop per line unit |
| COMPLIANCE | Tested per GR-1089, ATIS-0600026.2010(R2015), UL- 497, applicable GR-974 |