

MAQS G.fast Splitter with Dual Primary Protection Module

Model SA-7012-2001

NAME	ORDER NUMBER
MAQS G.fast Splitter with Dual Primary Protection Module	SA-7012-2001



BENEFITS

- G.fast Splitter and Dual Protection in single module
- Superior lightning and surge protection
- Backwards compatible to VDSL2 and ADSL2+

The MAQS Module provides both Line and POTS primary protection and splitter in one module that offer quick and easy configuration changes.

The combination of both GDT and Solid state primary protectors coordinate to offer superior lightning and surge protection.

The Splitter is specifically built for the demanding technology of G.fast by maximizing performance and data rates and is also backward compatible to VDSL2 and ADSL.

The Splitter module fits in any position on the 24-port mounting frame.

SPECIFICATIONS

DIMENSIONS	26.5 x 14.4 x 145.2 mm 1.04 x .57 x 5.72"
-------------------	---

OPERATING TEMPERATURE	-40 to +65 °C -40 to +149 °F
------------------------------	---------------------------------

WEIGHT	42.5g (1.5oz)
---------------	---------------

CAPACITY	1 Subscriber loop per line unit
-----------------	---------------------------------

COMPLIANCE	Tested per GR-1089, ATIS-0600026.2010(R2015), UL- 497, applicable GR-974
-------------------	--