
Central Office Connector Block Accessories

Model A0344522 A0310190 A0408552 A0321718 A0337661 A0386865 A0388387 A0359994 A0388388 A0388389



| NAME | ORDER NUMBER |
|---|--------------|
| 303-1213 Test Cord | A0344522 |
| 303-1019 Test Point Insulator (except C(G)-391) | A0310190 |
| Test Point Insulator C(G)- 391 only | A0408552 |
| 545-1137 Wire-wrap Terminal Cap | A0321718 |
| 377-1003 Mounting Bracket | A0337661 |
| C-303 Mounting Bar | A0386865 |
| 7 ft Universal Connector Mounting Bar | A0388387 |
| 8 ft Universal Connector Mounting Bar | A0359994 |
| 9 ft Universal Connector Mounting Bar | A0388388 |
| 11.5 ft Universal Connector Mounting Bar | A0388389 |

Test cords
Circuit Markers
Mounting Bars and Brackets
Universal Connector Mounting Bars




BENEFITS

- Convenient test access
- Rapid fault diagnosis
- Industry standard connectors
- Rugged, long-lasting materials

Test Cords

303-1213

This test cord is equipped with mini-test clips on one end and two insulated alligator clips on the other end.



Specifications / How to Order

| Product Code | Part Number | Description | Length m (ft) | Conductors | Termination | Standard Pack | Size mm (in.) | Weight kg (lb) |
|-----------------|----------------|-------------|---------------------|------------|--------------------------------------|------------------|--|----------------------|
| 303- 1213 | A0344522 | Test Cord | 0.53 (1.75) | 2 | Mini clips/two alligator clips | 1 | 25 x 25 x 51 (1 x 1 x 2) | 0.03 (0.06) |


Note: Order by Part Number

Circuit Markers

Comtest circuit markers are used to indicate Special Safeguarding Measures/Special Service Protection (SSM/SSP) circuits on the 303-family of connectors.

303-1019

The test point insulator button fits into the recesses on the test field to isolate the pairs from accidental contact by test points or during testing with a front tap shoe. The buttons are made of a red plastic material and are designed to snap into place to cover one test field contact. Not compatible with C(G)-391



Test-point insulator button for C(G)-391 only (not shown).

545-1137

The red-colored plastic cap is used to mark and prevent accidental access to wire-wrap terminals of special circuits. The cap is designed to fit snugly over a wire-wrap terminal. One is required for each terminal



Specifications / How to Order

| Product Code | Part Number | Description | Standard Pack | Size mm (in.) | Weight kg (lb) |
|-----------------|----------------|--|------------------|-------------------------------|-------------------|
| 303-1019 | A0310190 | Test Point Insulator (except C(G)-391) | 100 | 25 x 80 130 (1 x 3 x 5) | 0.03 (0.06) |
| A0408552 | A0408552 | Test Point Insulator C(G)- 391 only | 100 | 25 x 80 130 (1 x 3 x 5) | 0.03 (0.06) |
| 545-1137 | A0321718 | Wire-wrap Terminal Cap | 100 | 25 x 80 130 (1 x 3 x 5) | 0.03 (0.06) |


Note: Order by Part Number

Mounting Bars and Brackets

CNI provides mounting bars and brackets for various connector types and applications made of heavy gauge steel.

377-1003

Bracket for wall-mounting a single C-377, C-388 or C(G)-390 connector block.



Specifications / How to Order

| Product | Part | Description | Standard | Size mm | Weight kg |
|----------|----------|------------------|----------|--------------------------------------|----------------|
| Code | Number | | Pack | (in.) | (lb) |
| 377-1003 | A0337661 | Mounting Bracket | 1 | 260 x 100 x 80 (10.38 x 4 x 3) | 1.90 (4.25) |

Note: Order by Part Number

C(G)-303 and C(G)-310 Connector Blocks

Mounting bars are available for 7-, 8-, 9- and 11.5-ft high frames. Select the proper mounting bar by connector type and frame height.

How to Order - Mounting Bars for C(G)-303 and C(G)-310 Connector Blocks

| Product Code | Part Number | Connector Type | MDF Height m (ft.) | Length m (in.) | Connector Capacity | Standard Pack |
|------------------|----------------|-------------------|--------------------------|-------------------|-----------------------|------------------|
| 022-1078- 115 | A0386865 | C-303 | 2.13 (7) | 1651 (65) | 3 | 1 |

Note: Order by Part Number

Universal Connector Mounting Bars

Comtest Universal Adapter Bars accommodate the compact spacing dimensions of the C(G)-391, C(G)-390, C-388 and C-377 connectors. They are normally used by mounting them on the ends of the transverse arms of the distributing frame at 8 inch centers. They may also be mounted on existing verticals using the slots provided. All the bars are made of 3.4 mm (0.135 in.) thick x 38 mm (1.5 in.) wide plated steel. The mounting bar provides electrical conduction when the distributing frame is used to provide a ground path for the connectors.



How to Order

| Product Code | Part Number | MDF Height m (ft.) | Overall Length mm (in.) | Connector Capacity 377/388/390 | Connector Capacity 391 | Standard Pack |
|------------------|----------------|--------------------------|----------------------------------|--------------------------------------|------------------------------|------------------|
| 022-3917- 115 | A0388387 | 2.13 (7) | 1676 (66.60) | 6 | 7 | 1 |

| Product Code | Part Number | MDF Height m (ft.) | Overall Length mm (in.) | Connector Capacity 377/388/390 | Connector Capacity 391 | Standard Pack |
|------------------|----------------|--------------------------|----------------------------------|--------------------------------------|------------------------------|------------------|
| 022-3918- 115 | A0359994 | 2.44 (8) | 1956 (77.00) | 7 | 8 | 1 |
| 022-3919- 115 | A0388388 | 2.74 (9) | 2362 (93.00) | 8 | 10 | 1 |
| 022-3920- 115 | A0388389 | 3.51 (11.5) | 3114 (122.60) | 11 | 12 | 1 |

Note: Order by **Part Number**