

Full Bonded CPE VDSL2 Splitter

Product Name

Ordering Number

CPE-FB

SA-2208-0001



Carriers require alternative solutions as networks speed up, insisting high-bandwidth CPE response reach their preferred demarcation point. The CPE-FB simplifies and reduces installation time of bonded services in customer's home or business.

The Comtest Bonded CPE (CPE-FB) is a full dual low-pass filter designed to enable up to two POTS services to coexist with two-line bonded ADSL2+ or VDSL2 data signals up to 30MHz.

Standard bonded splitters simply pass the second pair through and leave it untreated. Our unique CPE-FB filters both pairs, thus supporting an additional POTS line or billing service on the second pair. In addition, treating the DSL signals on the second pair maximizes data rates to take full advantage of the bonded xDSL service.

Product Benefits

- Indoor Bonded VDSL2 POTS Splitter
- Supports up to two (2) POTS lines
- Backwards compatible to ADSL/2+
- Secondary lightning /surge suppression
- Compliant to Telcordia and CSA/UL Standards
- LINE connects to Gel filled Insulation Displacement Connectors (22AWG – 26AWG solid conductor)

Specifications

Dimensions	53mm x 98mm x 13mm [H x W x D] 2" x 3 7/8" x 1/2"
Operating Temperature	-40 to +65 °C -40 to +149 °F
Weight	70g (0.15lbs)
Communications Interface	Line 1 & 2: Gel-filled Insulation Displacement Connectors (IDC) Modem Pairs 1 & 2: RJ11 Phone Pairs 1 & 2: RJ11
Capacity	1 Two-pair bonded xDSL subscriber line 2 POTS lines
Compliance	T1.413, T1.424, ITU-T G.992.1, G.992.3, G.992.5, G.993.1 & G.993.2, CSA/UL 60950, FCC Part 68, CS03, GR1089 (Level 1 & 2 Surges and Power Fault)



V1 10/25/2017



comtestnetworks.com



sales@comtestnetworks.com



1.877.369.5499