

### Features

- Accepts 5-pin protector modules
- Wire-wrap for input and output wiring
- Lightweight and compact
- Wall mount
- Ground terminal on front panel
- ∎ ເຟຼີມ₀ UL Listed

## Applications

- Small remote cabinets
- Small pair count requirements
- PBX
- Data communications

## **BBT Building Terminal Series**

CNI Model BBT is a building terminal to provide protection for circuits being provided on twisted pair. The BBT uses standard 5-pin protector modules to provide overvoltage protection from harmful transient voltage surges such as lightning and power cross transients. The input cable is wired to the input row of wire-wrap pins. The pins can support two wire-wraps per piece. The output wire is wired to a row of output wire-wrap pins. The input, output and 5-pin protector module locations are easily identifiable. Internal wiring of #26AWG is designed to provide a fuse-link. The unit is compact and wall mounted using two screws. Using adapter bars, the unit can also be mounted on a 19 or 23 inch relay rack or frame. The BBT has an easily accessible ground terminal on the front plate that will hold #14AWG to #6AWG ground wire. The BBT series building terminal can be supplied with no modules or with 5-pin protector modules.

#### How to Order

	BB	T ·	- (	025	- 1	-	11	- 3	<b>KX</b> -	• xx
Model Number Designator										
Pair Count										
Location1 = Indoor										
Input Connection										
Output Connection 1 = Wire-wrap										
TLPU Options (see charts below)										
Customer Specific Designator										

#### TLPU Options

	3-Type Overvoltage				
(Blank)	No TLPU Included	*			
01	2410-31-G-MSP	Black			
02	2410-31-G-MSP-T	Black, Test			
03	2410-33-G-MSP	Red			
04	2410-33-G-BC	Red, Balanced Capacitance			
05	2410-310-G-BC	Yellow, Balanced Capacitance			
06	2410-71-G-BC	Short, Black, Balanced Capacitance			
07	2410-76-G-BC	Short, Blue, Balanced Capacitance			
08	2420-31-G	Black			
09	2420-31-G-T	Black, Test			
10	2420-33-G	Red			
11	2420-76-G	Short, Blue			


	4-Type Sneak Current				
12	2430-41-G	Black			
13	2430-43-G	Red			
14	2440-41-G	Black			
15	2440-43-G	Red			
16	A0341959	Black			
17	303M-09H3GH	Red			
18	A0365896	Black			
19	A0341960	Red			
20	A0353716	Black			
21	A0361533	Black			
22	A0353717	Red			


Related product: 7009 Series enclosures.

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications.

# **BBT Building Terminal Series**

#### Product Dimensions





DIMENSIONS: MM (INCHES)

Rev 06/04/2020

Comtest Networks Inc. (CNI) comtestnetworks.com

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications.